

COMMUNICATION METHOD OF SUPPLYING INFORMATION IN  
INTELLIGENT NETWORK AND APPARATUS THEREFOR

• BACKGROUND OF THE INVENTION

The present invention relates to an intelligent network for providing a supplement service to a communication network including a telephone network, and more particularly to a communication method suitable for realizing a service to provide information so that home users can receive various information and an apparatus therefor.


Typical examples of prior art information providing services through a public communication network are time announcement (telephone number 117) and weather forecast (telephone number 177) through the public telephone network. In those services, dedicated circuits (called talky trunks) are provided in a switching system of the telephone network, and when a subscriber who wants the service dials a special number (for example, 117 or 177 mentioned above), the switching system operates to connect it to the dedicated circuit so that audio information such as the weather forecast sent from the dedicated circuit is directly passed to the telephone set. In order to accomplish the service, it is necessary for all of the switching systems to be provided with the dedicated circuits. When it is desired to change the content of the service, for example, when the information of the weather forecast is to be changed, the recorded

2

content of each switching system must be changed.  
Accordingly, in this system, the more the number of  
services to be provided increases, the more difficult are  
the addition of new services and the change of the  
5 contents of the services.

In order to solve the above problems and permit  
flexible providing of various services, it has become  
common to construct an intelligent network. In this  
system, a transmission layer for transmitting audio  
10 information and an intelligent layer for transmitting  
control information required to realize the service are  
provided, and various facilities required to realize the  
service (for example, a database) is installed in the  
intelligent layer. Detail of the intelligent network is  
15 described, for example, in an article "Intelligent  
Network and Network Operation" (Chapter 1.3.2, pages  
19-21, by Minoru Akiyama et al, Corona Publishing Co.).

An example of the services which use the  
intelligent network is an information providing service  
20 charged to a service provider or a so-called #800  
service. In this service, the information provider  
contracts with a network provider to get a special number  
(888-xxxxxx) from the network provider. When a general  
telephone subscriber dials to that special number, the  
25 network provider collects a charge from the information  
provider rather than the subscriber who dialed (caller).  
In order to realize the service, the network provider  
installs in the intelligent layer a database for



allocating a connection destination based on the special number, a database for recording the charges, a mechanism for controlling the transmission network to connect the caller to the information provider (called a connection  
5 control point) and a database for storing control information to operate the mechanism. The addition and the change of the services are readily attained by changing the contents of those databases.

An example of the intelligent network services  
10 which use the databases is disclosed in U.S. Patent No. 4,191,860 "Database Communication Call Processing Method" to R.P. Weber. In the illustrated drawing of the prior art, DATABASE and STP are connected through CCIS which is a common channel signaling network to form an intelligent  
15 network.

Examples of the information services charged to the service provider would be news, more detailed weather forecast, guide to movies, recruiting information, road information and event information.

20 In the above prior art, when a general telephone subscriber wants to receive an information providing service, he/she dials to the information provider to get the information. For example, when he/she wants to get news of the day, he/she dials to the information  
25 provider who provides the news providing service, and when he/she then wants to get weather forecast, he/she dials to the information provider of the weather forecast. It may be convenient that desired information is

4

available at a desired time but it takes time and handling accordingly. On the other hand, there are information providing media such as television. In this system, since the information flows in one way, it is difficult  
5 to get desired information at a desired time although it does not take much time and handling.

In general, it frequently occurs that some information is daily needed at some time in a usual life. That information and that time vary from person to  
10 person.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide an information providing service which permits the acquisition of desired information at a desired time  
15 through an intelligent network in order to comply with the desire which varies from person to person, and which permits programming of the information as desired rather than fixed information such as a television program.

More specifically, a service user first  
a 20 registers ~~register~~ to a network provider a program indicating a time band and a content of service he/she wants to receive (registration of program). In accordance with the program, the network provider automatically connects the designated information provider to the service user  
25 at the designated time without requiring the intervention of the service user to realize the information providing.

In order to solve the above problems, a

5

database in which the program for the service user to  
acquire the information is to be registered is provided  
in the intelligent network comprising service control  
points (SCPs) for controlling the information processing  
5 and the databases, terminals of the service users,  
switching systems, service switching points (SSPs) for  
transmitting service requests provided from the service  
users through the switching systems to the SCPs through  
control signals lines such as a common channel signaling  
10 network and transmitting control commands from the SCPs  
to the switching system, and service management systems  
(SMSs) which are management systems for the SCPs and the  
SSPs and connected to a network management terminal  
through a communication network such as a packet data  
15 network for adding and changing the service functions.  
The service user can directly or indirectly set and/or  
change the data on the database. The program may be  
registered even when the database is provided in one or  
more of the SCP, the SSP and a terminal of the service  
20 user (service user terminal) in the intelligent network.

In accordance with the present invention, the  
service user can receive the information providing  
service which the service user has programmed by  
himself/herself.

25 The registration of the program is carried out  
in the following manner. The service user registers any  
number of combinations of the telephone numbers of the  
information providers from which he/she wants to get the

6

information and the times at which he/she wants to receive the information services in a database for registering the program on the network.

The services are provided in the following manner. The service management system (SMS) has a service scenario which describes the definitions and procedures of the services. When the time which the service user has registered is reached, the service control point (SCP) transmits a service request to the service switching point (SSP) by the data of the program which the service user has registered. In response to the request by the SCP, the SSP connects the terminal of the service user to the information provider to start the information providing service.

#### 15 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows an embodiment of an information providing network of the present invention,

Fig. 2 shows a block diagram of hardware of Fig. 1,

20 Fig. 3 shows a flow chart of a service scenario used in the information providing network of Fig. 1,

Fig. 4 shows an operation sequence of the information providing network of Fig. 1,

Fig. 5 shows another embodiment of the information providing network of the present invention,

Fig. 6 shows a block diagram of hardware of a terminal of Fig. 5,

7

Fig. 7 shows a flow chart of a service scenario used in the information providing network of Fig. 5,

Fig. 8 shows an operation sequence of the information providing network of Fig. 5,

5 Fig. 9 shows other embodiment of the information providing network of the present invention,

Fig. 10 shows a flow chart of a service scenario used in the information providing network of Fig. 9, and

10 Fig. 11 shows an operation sequence of the information providing network of Fig. 9.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

The information providing network of the present invention is now explained with reference to the  
15 drawings.

In one embodiment of the present invention, a user database is installed in a storage in a service switching point (SSP) to implement the programming of an information providing service.

20 Fig. 1 shows a configuration of an information providing network. In Fig. 1, numeral 101 denotes a service control point (SCP), numeral 102 denotes a service control database provided in a storage in the SCP, numerals 1031 ~ 1034 denote switching systems,  
25 numerals 1041 ~ 1044 denote service switching points (SSP's), numerals 1051 ~ 1052 denote user databases, numerals 1061 ~ 1062 denote service user terminals,

8



numerals 1071 ~ 1072 denote information provider terminals, numeral 109 denotes a service management system (SMS), numeral 110 denotes a network management terminal, and numeral 111 denotes a service management database provided in a storage of the SMS 109. In Fig. 1, the SCP 101, the service control database 102, the SMS 109, the network management terminal 110 and the service management database 111 belong to an intelligent layer, and the switching systems 1031 ~ 1034, the SSP's 1041 ~ 1044, the user databases 1051 ~ 1052 in the SSP's, the service user terminals 1061 ~ 1062 and the information provider terminals 1071 ~ 1072 belong to a transmission layer.

The network manager can set and change the data of the databases in the SMS 109 through the network management terminal 110. A plurality of SCP's are provided and they are connected by the network.

Fig. 2 shows a block diagram of hardware of the SMS 109, the SCP 101 and the SSP 104.

In Fig. 2, the SMS 109 comprises a control unit 51 including a CPU for controlling an overall operation of the SMS, a storage 53 and an interface 52 for the connection with the network in the intelligent layer. The service management database 111 is provided in the storage 53. The control unit 51 is connected to the network management terminal 110.

The SCP 101 comprises an interface 54 for the connection with the network in the intelligent layer, a

9

control unit 55 including a CPU for controlling an overall operation of the SCP, a timer circuit 56 for collating a current time to a service providing time, a storage 57 and a common channel signaling interface 58  
5 for the connection with a common channel signaling network. The service control database 102 is provided in the storage 57.

The SSP 1041 comprises a common channel signaling interface 59 for the connection with the common  
10 channel signaling network, a control unit 60 including a CPU for controlling an overall operation of the SSP and a storage 61. The user database 1051 is provided in the storage 61 and the control unit 60 is connected to the switching systems.

15 Fig. 3 shows a service scenario in the service management database 111. The service scenario is also programmed with the same content in the service control database, for example, 102, in the SCP which is under the control of the SMS 109, and when the service scenario in  
20 the service management database 111 is changed by a command from the network management terminal 110, the service scenario in the SCP is also automatically changed in the same manner. The SCP issues a connection operation command to a subsidiary node in accordance with the  
25 service scenario.

The flow of the service scenario of Fig. 3 is explained below.

In a step 71, the connection number and the

10

time registered in the user database are read into the service control database in the SCP.

In a step 72, a current time is continuously collated to the service start time by the timer circuit  
5 in the SCP.


In a step 73, when the service start time is reached, the lines of service user and the information provider are connected.

In a step 74, a current time is continuously  
10 collated to the service end time by the timer circuit in the SCP.

In a step 75, when the service end time is reached, the lines of the service user and the information provider are disconnected.

15 Fig. 4 shows an operation sequence of the information providing network of the invention. The operation is now explained.

In Fig. 1, the service user registers the connection number (usually a telephone number) which is  
20 the terminal number of the information provider and the start and end times of information providing on the user database 1051 through the service user terminal 1061 (201 in Fig. 4). To register them, a special number for the registration is predetermined and the service user dials  
25 that number and interactively registers the program. In order to prevent unauthorized third parties from using the service or accessing to the user database without permission, a secret number preset by the service user



may be required in the registration. The user database stores the service registration status for each service user as shown in Fig. 1. For example, the user of the terminal 1061 may register the service user telephone number 11-111, the desired service time 7:05 to 7:10 and the connection destination telephone number 33-333.

The SCP 101 reads in the data of the user databases 1051 ~ 1052 in the subsidiary SSPs in a step 71 of Fig. 3 (202 in Fig. 2), applies necessary conversion thereto and holds the data on the service control database 102 as shown in Fig. 1. The service control database 102 holds the registration data by sorting it in the order of service start time, for example, to facilitate the connection of the terminal.

The SCP 101 has timer circuit 56 which collates the current time to the service start time registered on the service control database 102 in a step 72, and when the designated time is reached, the SCP 101 transfers the connection number or the telephone number of the service user terminal and the telephone number of the information provider terminal to the SSP which is located at the same position as that of the switching system to which the service user terminal is connected. For example, when the current time is 7:05, the SCP 101 transfers the information required for the connection to the SSP 1041 to command the connection thereof (203 in Fig. 2). The SSP 1041 calls both the service user terminal 1061 and the information provider terminal 1071 by the command

12

a  
a  
a  
from the SCP 101 (204 and 205 in Fig. <sup>4</sup>1<sup>2</sup>), and after the  
acknowledgements by the both terminals (206 and 207 in  
Fig. <sup>4</sup>1<sup>2</sup>), it connects the both terminals (208 in Fig. <sup>4</sup>1<sup>2</sup>).  
Then, the SCP 101 collates the current time to the  
5 service end time by the timer circuit 56 in a step 74,  
and when the service end time is reached, the SCP 101  
issues a disconnection command in a step 75 (209 in Fig.  
<sup>4</sup>1<sup>2</sup>) and the SSP 1041 releases the line connection (210 and  
211 in Fig. 2). When the service user wants to change  
10 the program content such as the time to acquire the  
information or the connection destination, he/she may  
change the content of the user database from the service  
user terminal in the same manner as that for the  
registration.

15           The registration of the program may be changed  
not only through the service user terminal 1061 but also  
by any one of the terminals in the network which has a  
required function.

20           In the present embodiment, since the user  
database which may be directly accessed by the service  
user is provided in each SSP which accommodates that  
service user, the management is facilitated.

25           Further, since the service user does not  
directly access to the network resources such as the  
service management database and the service control  
database, there is no risk of destroy of the network  
resources by the misoperation of the service user. On  
the other hand, the SCP has the database for the control

15

of the service of the network. The data may be duplicate with that of the user database but since the control of the overall network is necessary to provide the service, the exchange of the data in the low level layer does not frequently occur by the provision of the data in the high level layer and the efficiency is improved.

In another embodiment of the present invention, a user database is installed in a terminal to implement the information providing service.

a 10 Fig. 5 shows a configuration of the information providing network in <sup>this</sup> ~~the present~~ embodiment. In Fig. 5, numerals 1031 ~ 1034 denote switching systems, numerals 1061 ~ 1062 denote service user terminals, numerals 1071 ~ 1072 denote information provider terminals, 15 numerals 1081 ~ 1082 denote user database added to the service user terminals.

Fig. 6 shows a block diagram of hardware of the service user terminal 1061.

The service user terminal 1061 comprises a 20 telephone set circuit 62, a control unit 63, a timer circuit 64 and a storage 65. The control unit 63 is connected to other units in the terminal and controls the function of the terminal by a CPU. The telephone set circuit 62 is connected to the external switching system. 25 The timer circuit 64 collates the current time to the service start time and the service end time. The storage 65 is provided with a user database 1081.

Fig. 7 shows a service scenario provided in the

14

user database 1081. The service user terminal 1061 issues a connection command for the service providing in accordance with the service scenario.

A flow of the service scenario of Fig. 7 is  
5 explained below.

In a step 76, the current time is continuously collated to the service start time by the timer circuit.<sup>64</sup>

In a step 77, when the service start time is reached, the information provider terminal<sup>1071</sup> is called to  
10 connect the line.

In a step 78, the current time is continuously collated to the service end time.

In a step 79, when the service time is reached, the line between the user and the information provider<sup>1071</sup> is  
15 disconnected.

Fig. 8 shows an operation sequence of the present embodiment.

The service user registers the connection destination number (usually a telephone number) which is  
20 the terminal number of the information provider and the desired service time on the user database 1081 (301 in Fig. 8). When the designated time is reached, the terminal 1061 automatically calls the information provider 1071 in steps 76 and 77 of Fig. 7 (302 in Fig. 8). By  
25 the acknowledgement of the information provider 1071 (303 in Fig. 8), the service user can acquire the desired information (208 in Fig. 8). When the designated service end time is reached, the terminal 1061 disconnects the

15



call in steps 78 and 79 (305 in Fig. 8).

In accordance with the present embodiment, the intelligent layer is not required and each service user terminal need only maintain the data of its own and the improvements is attained in terms of both security and economy.

a Fig. 9 shows a configuration of <sup>yet another</sup> ~~other~~ embodiment of the information providing network of the present invention.

10 In the present embodiment, a database is provided in only the intelligent layer of the intelligent network.

The configuration of the network of the transmission layer is identical to that of Fig. 1 and the like elements are designated by the like numerals. The configuration of the hardware of the SMS and the SCP are identical to that of Fig. 2 except the contents of the databases. The service control database 102 is provided with a table 131 in which the telephone numbers of the service users, the service providing times and the telephone numbers of the service providers are registered.

Fig. 10 shows a flow chart of the service scenario of the embodiment of Fig. 9. The identical content of the service scenario is written in the databases of the SMS and the SCP, and when the service scenario in the SMS is changed by the network management terminal 110, the service scenario in the SCP is also changed.



A flow of the service scenario of Fig. 10 is explained below.

The current time is collated to the service start time by the timer 56 (Fig. 4) (step 91), and when  
5 the service start time is reached, the line between the user and the information provider is connected (step 92). Then, the current time is collated to the service end time by the timer 56 (step 93), and when the service end time is reached, the line between the user and the infor-  
10 mation provider is disconnected (step 94) to terminate the service.

Fig. 11 shows an operation sequence of the information providing network carried out in accordance with the service scenario of Fig. 10.

15 The service user dials to the network provider to report his/her telephone number or identification number, the desired service time and the desired information provider number (401). The network provider registers the content of the report in the table 131 on  
20 the service control database 102 in the SCP 101 through the SMS 109 by the network management terminal 110 (402).

The SCP 101 collates the current time to the service start time in the step 91, and when the service start time is reached, it sends the terminal number of  
25 the service user and the terminal number of the information provider to the SSP 101 to which the service user terminal is connected in the step 92 (203). In response to the call command, the switching system connects the

service user terminal 1061 and the information provider terminal 1071 (204 to 208). The SCP 101 collates the current time to the service end time in the step 93, and when the service end time is reached, it issues a line  
5 disconnect command to the SSP 101 (209). In response to the disconnect command, the switching system disconnects the line (210, 211).

In accordance with the present embodiment, the databases may be centrally installed and efficient and  
10 economic service can be provided in a small scale network.

In the above embodiments, a sequence of the termination of the service in response to the disconnection of the line from the information provider may be  
15 included.

In the above embodiments, the network is constructed to provide the information providing services such that at least one database which allows the programmed edition of the information providers and the  
20 information providing times by the service user or the network provider is arranged in the intelligent network so that the service user can get the desired information at the desired time. The present invention is not restricted by the information to be served (the transmission rate and the content) and the facilities of the  
25 communication network (the switching system and the transmission apparatus), and it is applicable from the low speed narrow band communication such as <sup>an</sup>~~the~~ audio

a  
18

a  
a  
a  
10  
15

providing service such as the weather forecast to ~~the~~  
high speed wide band communication such as <sup>a</sup>~~the~~ multimedia  
information providing service including video image and  
voice. For example, in the embodiments, the service user  
5 terminal may be a multimedia information terminal or a  
television set, the information provider may be a cable  
television company who provides multi-channel programs  
and the switching system and the transmission facilities  
may be ATM telecommunication apparatus suitable for ~~the~~  
10 high speed broad band communication so that a video on-  
demand service (for example, disclosed in Nikkei  
Electronics, No. 574, pages 102 ~ 107, Feb. 15, 1993)  
which has recently been demanded in the CATV service can  
be readily realized on the public telecommunication  
15 network without requiring dedicated facilities and  
economic information providing service is attained.